

GreenWatts Solar Panels

# SUPERIOR PERFORMANCE & RELIABILITY

## HS66-F-710-MN(N)

HT66-210(ND)-F-710

Solar Panel Monocrystalline  
Double Glass TopCon Module

### HIGHLIGHTS

- Maximum Power Output: 710W
- Maximum Efficiency: 22.9%
- Number of Cells: 132 (6x22)
- Bifaciality: 80 ±5 %



### Optimized for High Voltage Systems

- Specifically designed to align with advanced high voltage system requirements.
- Maximum Efficiency up to 22.9%
- Cost effective solutions designed to offer a competitive balance of system cost suitable for utility-scale projects.



### Enhanced Efficiency with Half Cut Cell Technology

- Minimizes resistive losses and reduces shading impact, boosting overall efficiency.
- Ensures long term performance against Potential-Induced Degradation.



### Durability in Extreme Conditions

- Engineered to endure harsh environmental conditions, such as extreme temperatures, high humidity, salt, mist, and sand.
- Supports up to 5400 Pa for snow loads and 2400 Pa for wind loads, reinforcing module reliability in diverse environmental conditions.

### High Reliability



Certification:



ISO 9001  
ISO 14001  
ISO 45001

UL 61730

IEC 61215  
IEC 61730



P: +1 (619) 354-3094  
E: sales@greenwatts.solar  
W: greenwatts.solar

Los Angeles  
9255 Sunset Blvd, Los  
Angeles, CA 90069

San Diego  
1094 Cudahy Place, Suite 212,  
San Diego, CA 92110

## MECHANICAL CHARACTERISTICS

Solar Cell	Monocrystalline 210 x 210 mm
Number of Cells	132 (6x22)
Dimensions	2384 x 1303 x 35mm 93.86 x 51.30 x 1.38 inches
Weight	38.5 kg   84,878 lb
Front Glass	High transmission coated tempered glass
Back Glass	Heat strengthened glass
Frame	Anodized aluminium alloy
Junction Box	IP68 Rated
Output Cables	4mm <sup>2</sup>   0,00620001 in <sup>2</sup> (IEC)
Connectors	MC4
Maximum Power in STC (Pmax)	710 W
Maximum Operating Voltage (Vmp)	41.30 V
Maximum Operating Current (Imp)	17.20 A
Open Circuit Voltage (Voc)	48.20 V
Short Circuit Current (Isc)	18.45 A
Module efficiency	22.9%
Operating Temperature of the module	-40°C ~ +85°C
Maximum System Voltage	1500V DC
Power Tolerance	0 ~ +3%
STC	Irradiance 1000W/m <sup>2</sup> , Cell Temperature 25°C, Air Mass 1.5

## TEMPERATURE CHARACTERISTICS

NMOT	43 ±2 °C 109.4 ±35.6 °F
Temperature Coefficient of PMAX	-0.29% /°C
Temperature Coefficient of VOC	-0.25% /°C
Temperature Coefficient of ISC	+0.046% /°C



## PACKING CONFIGURATION

Module per Box	31 Pieces
Module per 40' Container	558 Pieces


## ADDITIONAL INFORMATION

Snow and wind loads	Wind - 2400Pa Snow - 5400Pa
IEC Protection Class (I, II, III)	II
Max installation altitude	2000m
Allow roof pitch/angle	Minimum 10 degrees
Max Series Fuse Rating	35A
Fire Rating	Type 29
Front Cover (material / glass thickness)	AR 2.0mm
Back Cover (material / glass thickness)	Normal glass 2.0mm
Bifaciality	80 ±5 %


## ENGINEERING DRAWING



## IxV CURVE



## PERFORMANCE WARRANTY



\*Specific information is referred to the product quality guarantee



P: +1 (619) 354-3094  
E: sales@greenwatts.solar  
W: greenwatts.solar

Los Angeles  
9255 Sunset Blvd, Los  
Angeles, CA 90069

San Diego  
1094 Cudahy Place, Suite 212,  
San Diego, CA 92110